

Data Sheet Sallegra® IP Dali Gateway

Sallegra® IP Dali Gateway



The Sallegra® IP Dali Gateway has an integrated 10 / 100Mbit network interface and DALI power supply. It acts as an interface module for connecting DALI systems to the Sallegra building automation systems. In addition, it convinces with its simple mounting on a DIN rail and 5-year guarantee.

Technical specifications:	
Voltage range	12V DC
Connection	Dali Bus A/B
Adresses	Max. 64 DALI participants
Power / standby power	1-6 W/ 1 W
Ethernet	TCP/IP 10/100MB
Output voltage DC	16 V +/- 5%
Operative temperature	0 to + 50 °C
Storage temperature	-20 to +60°C
Humidity	10-90% (not condensating)
Dimensions	35 mm x 91 mm x 60 mm
Weight	approx. 90 g
Certification	IP 20

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch
Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as „front accessible“ can be accessed by the customer.