



Data Sheet Sallegra® M-bus/TCP Gateway

Sallegra® M-bus/TCP Gateway



The Sallegra® M-Bus / TCP gateway enables communication between up to 80 M-Bus participants and Ethernet-based devices. He implements the M-Bus physics on Ethernet. It must be configured with the associated PC software via the Ethernet interface. Installation is simple and reliable on a DIN rail.

Technical data	
Interfaces	1x M-bus (terminals), 1x Ethernet (RJ-45 socket)
M-Bus / Ethernet data rate	Max. 38.400 bps/ 10/100 Mbit/s
LEDs	5x Signal display for supply and communication
Power consumption	8 watts/VA
Operative temperature	-40°C to +85°C
Humidity	10% to 80%, not condensating
Mounting	On a DIN rail
Dimensions	71mm x 95mm x 60mm
Weight	ca. 200g
Satelco article number	11613

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch
Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as „front accessible“ can be accessed by the customer.

Data Sheet Sallegra® M-Bus Power Supply



Sallegra® M-Bus Power Supply

Power Supply for M-Bus Master device that supports up to 80 slaves.

Technical data	
Input voltage range	110/220V AC
Output voltage	24VDC / 9W
LED	Green = Output Voltage
Other protections	Overcurrent Input Protection Overtension Input Protection Undertension Input Protection Overtemperature Protection
Dimensions	53 x 60 x 95 (D x W x H)
Weight	200 g
Satelco article number	11614

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch
Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as „front accessible“ can be accessed by the customer.