



Data Sheet Sallegra® IP RS-485 Gateway Series 2020



Sallegra® IP RS-485 Gateway Series 2020

With the Sallegra® IP bus coupler, you can easily integrate Sallegra® BUS devices in a LAN network. The bus coupler acts as an interface adapter between Ethernet and Sallegra® bus systems. It communicates in both directions, is protocol-independent and tolerates high temperature ranges. In addition, it convinces with its simple mounting on a DIN top-hat rail.

swissmade 

| Technical data: | |
|-----------------------|---|
| Network protocols | TCP/IP |
| Interfaces | 1x Ethernet RJ45, 1x Sallegra®-Bus |
| Power supply | Min. 12 bis max. 35 V DC 3,5 W bei 24 DC; Min. 8 bis max. 24 V AC, 3,5 VA, 50/60 Hz |
| LED display | 5x signal display for supply and communication |
| Operative temperature | -40°C to + 85 °C |
| Humidity | 10-80% (not condensating) |
| Dimensions | 71 mm x 95 mm x 60 mm |
| Weight | approx. 200 g |
| Mounting | On an DIN Rail 35mm |

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch
Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as „front accessible“ can be accessed by the customer.