



Datasheet Automation Controller Entry Serie 2020

Sallegra® Automation Controller Entry



swissmade 

- **KNX Interface integrated**
- **Sallegra® operating system, can be easily expanded with countless software functions at any time**
- **Function as a multi-controller (backup, redundancy, load sharing), also across locations**

Technical data:	
Processor	Intel Atom E3825 Dual Core with 1.33 GHz clock frequency
Operating system	Sallegra® based on Fedora Linux
Power supply	12 V DC ±20 % via 3-pole connection terminal
Current intake	Typ 550mA
Power recording	6.6 VA
Interfaces	
LAN1	Gigabit Ethernet interface to 8-pole FCC RJ-45 plug
RS232	1x serial COM interface, RS232 level, electrically isolated, 4-wire on terminal
RS485	3x serial COM interface, RS485 level, electrically isolated, on terminal
<u>KNX</u>	Slot for KNX module, incl. terminal block
USB	2x USB 2.0 host interface on a 4-pin USB connector type A
Battery	Battery backup holder for CR1632 button cell
Inputs	4x digital inputs, 12 V DC, current drawing, electrically isolated, LED display on terminal
Outputs	4x bistable relay outputs (NO/NC), 230 V AC / 16 A, electrically isolated, LED display on terminal
Audio	Audio output, not amplified supports audio signals in the frequency range from 300 - 3400 Hz
Memory	
External memory	MicroSD card up to 2GB, SDHC cards up to 32GB
Fixed memory	16 GB eMMC
Main memory	4 GB DDR3
Watchdog	Parameterisable via software
Real Time Clock	with battery backup
Configuration	with the Sallegra® Configurator
Dimensions	212 x 90 x 58 mm / 380 gr.
Protection class	IP20
Environmental conditions	
Operating temperature	0° C - +55° C
Storage temperature	0° C - +70° C
Humidity	10% - 90% (no condensation)
Mounting	DIN top-hat rail TS35, EN50022
Conformity	CE

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

* Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.