

Dual humidity and temperature sensor VT490



- High-quality humidity and temperature sensor
- Sensor connection relative humidity with 4-wire patch cable
- Automatic recognition with the Autosense function
- Display in the web interface
- Incl. RJ11 connection cable and fixing material

Communication interface	CAN bus
Input/Output terminals	x2 RJ11 6P4C-Ports
Daisy-Chain-Sensor	CAN bus chain
Max. Distance from the unit	225m
LED indicators	Red / Green
T accuracy	±0,4 °C (max), -10 to 85 °C
RH accuracy	± 3% RH (max), 0-80% RH
Resolution	0,1 °C
Working temperature	-40 bis +125 °C
Humidity	0 to 95 % operating range
Power input	12V DC, 1A
Power consumption	1 Watt
Dimensions	68 x 47 x 26 mm
Weight	160 g
Mounting	Desktop, Wall mount
HS-Code	9025 11 800
Satelco Article number	11107

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch

*Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.