

Satelco Access sensor door contact VT530

When installed on doors, windows, etc., the sensor checks the status of the door, window for open/closed.



- Daisy-Chain-Sensor
- Monitoring of doors in important rooms and facilities
- Monitoring of important server, network cabinets
- Monitoring of rolling gates -open/closed
- Monitoring of cabinets, switch cabinets
- Monitoring of branch offices, unmanned technical sites

Dimension	60 × 18 × 18 mm (L x W x H)
Power Consumption	60 MW
Operating Temperature	Min -10° C - Max. +80° C
Mounting	Mounting Bracket included
Max. Distance from the Unit	150 m
Weight	106 g
HS-Code	8531 10 300
Inputs Terminals	RJ-12 / RJ-11
Satelco Article number	11174

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch

*Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.