

Satelco Vibration Sensor VT540

SNMP traps can also be sent to building or network management software when vibrations or shocks are detected.



- Detection of vibrations, shocks
- Detection of vibrations in the technology or server cabinet
- Alarm for shocks and impacts of backup and storage systems
- Monitoring of vending machine (e.g. ticket machines, cash machines)
- Monitoring of windows and glass doors
- Monitoring of plasterboard and wooden walls

When mounted on walls, windows, etc. the sensor controls the vibration.

Chain connection is possible.

Dimension	60×18×18 mm (L x W x H)
Weight	60 gr
Power consumption	60MW
Operating temperature	Min. -10° C - Max.+80° C
Mounting	Mounting bracket included
Package contains	Cable RJ11/RJ12 to RJ11/RJ12, 2m, mounting bracket, screw 1pce. M5
Special features	Daisy chain sensor, max distance from unit 150 m
Inputs	RJ-12 / RJ-11 Terminals
Satelco Article number	11114

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch

*Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.