

Smoke detector VT560



- Sensor connection with RJ12 patch cable
- Early detection of fire and smoke
- Cascadable (general alarm only!)
- Display in the web interface
- Incl. 2m RJ12 connection cable and fastening material
- Analogue
- The unit consists of a compact plastic housing with ventilation openings

The maximum number of sensors and the maximum length can be extended with the VT408 / sensor extension unit.

Inputs Terminals	RJ-12 connectors X2
Max. Distance from unit	150m
Display status	Error LED
Special features	Daisy Chain - Sensitivity 0.05 - 0.2 Db/M
HS Code	8531 10 950
Operating temperature	Min. -10° C - Max.+80° C
Power consumption	100 MW
Dimension	(diameter, height) Ø100×45 Mm
Weight	290 gr
Mounting	Mounting bracket included
Satelco Article number	11383

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch
 *Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.