

Satelco Point Water Detector VT590



- Notification in case of water leakage in the server room
- Monitoring of water leakage from defective water spray extinguishing systems
- Detection of water damage in research, production and logistic environments
- Detection of condensate formation in the raised floor of the server room and data center
- Detection of water damage in raised floor of gymnasiums and sports halls
- Monitoring the condensate tank of the air conditioner
- Monitoring of the condensate tray (collecting tank) of heat exchangers
- Notification in case of leakage of air humidification and sprinkler systems
- Monitoring of heating systems
- Detection of water leakage from swimming pools, showers and toilets

Attention!

Metal cores are water detectors that are mounted strictly downwards as close to the ground as possible.

Dimension	60 x 18 x 18mm (L x W x H)
Weight	125 g
Consumption	60 MW
Operating temperature	Min. - 10° C- Max. + 80° C
Operating humidity	5 to 95% non-condensing
Mounting	Wall mounting, incl. Bracket
Max. Distance to the unit	100 m
HS-Code	9025 80 400
Special features	3m cable
Inputs	Rj11 6P4C terminals
Satelco Article number	11117

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch
 *Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.