



- Unique design
- Communication over telecom base lines
- Calling from entrance door to you office telephones

Telephone based door communicator

2N Vario is a door entry system which meets the highest demands and is of a modern design. This user-friendly door phone replaces door systems and offers many additional features.

2N Vario can be connected to any analog PBX extension available on the market (. As a result of its modularity it enables the creation of customised solutions according to the user's needs, not only in terms of its size, but also with various control elements and functions. Each basic module can be equipped with a camera, display or card reader. 2N is made of high-quality stainless steel, and its flat design makes possible installation without cutting into the wall. The main advantages of 2N door entry solution include easy installation, state of art functions and a modern design.

Highlights :

- Reachable from anywhere
- User friendly
- Unique design
- Modularity
- Useful as a wall phone (by using the keypad)
- Code lock

Features:

- Connect via analog phone line
- Audio, video, keypad and RFID key card reader in one
- Remote control and programming
- User announcements and acoustic signals
- Easy installation
- Weather resistance – Marine Grade Steel case with IP 53 cover
- Additional switch (potential-free contact)



All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

Technical Data:	
Connection with PBX	FXS-(internal) analogue telephone line according to standards CCITT
Buttons	
Quick dial buttons	stainless steel
Number of buttons	1, 3 or 6 and up to 54 using extenders
Numeric keypad	optional
Cover	
	External environment with sufficient rain protection
Audio	
	Half-duplex
Mircophone	1 integrated microphone
Loadspeaker	1W
Interface	
Power supply	From telephone line
DC voltage drop	< 8V (I=25mA)
(off-hook)	< 16V (I=50mA)
Dialling	Impulse/tone
Backlight – rated voltage	12V
Switch-max. voltage/current	Max. 48V/1A AC
Mechanical	
Operating temperature range	-20°C – 60°C
Dimensions	210x100x29 mm
Protection level	IP53

* warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. /

NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.