

Extensions & information modules



Helios add-on 8 x 1 buttons
Add-on module with 8 buttons,
LED lighting



Helios add-on 8 x 2 buttons
Add-on module with 16 buttons,
LED lighting



Helios Infopanel
Without button function,
LED lighting

Weather protection & assembly frame



Helios in-wall housing UP for 1 module
In-wall housing for indoor
installation



**Helios in-wall housing with
UP weather protection frame
for 1 module**
In-wall housing for outdoor or
indoor installation



**Helios weather protection
frame AP for 1 module**
Roof for outdoor installation



**Helios in-wall housing UP
for 2 modules**
In-wall housing for indoor
installation



**Helios in-wall housing with
UP weather protection frame
for 2 modules**
In-wall housing for indoor or
outdoor installation



**Helios weather protection
frame for 2 modules**
Roof for outdoor installation


Accessories



**Helios additional button with
nameplate - single**
Additional button with nameplate
(Vario 1 & 3 buttons)



**Helios additional button with
nameplate - double**
Additional button with
nameplate (Vario 3 x 2 buttons)



Helios Infopanel cover
Cover with nameplate for
information panel

Power supply unit/network accessories



DIN housing 12 V DC power supply
12 V DC / 1A or 12 V DC / 2A power supply unit



PoE Injector
Power over Ethernet injector (feed-in)
for Helios IP power supply via Ethernet



PoE Switch
PoE 8-port switch 10/100 Mbit with 4 PoE ports
for Helios IP power supply via Ethernet

Additional switching contact / electrical door lock



Helios IP additional switching contact
Mounting set for Helios IP Vario analogue basic
module, 2nd relay (dry contact)



Satelco Sallegra IP relay
Module with 4 channels, mounted on DIN rail
12 V DC supply



Helios Security Relay
External relay which is switched off with
a special code



Electric locking
Standard door lock
12 V / 0.6 A



Electric locking
Profi trogue spanner
Door lock Profi with trogue
spanner
12 V / 0.6 A



Electric locking
Profi mechanical MB changing
Door lock with mechanical MB
changing
12 V / 0.6 A

* Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.