



VoIP Gatekeeper Station

With the VoIP gatekeeper station from Satelco® you get a modern speakerphone which, thanks to full duplex, ensures clear and uninterrupted communication between 'inside' and 'outside'.

Technical features:

- VoIP communication via SIP 2.0
- Power supply via PoE (Power over Ethernet) or external power supply unit 12V DC/2 A
- Use of LAN / WAN network for administration, communication and control via web browser

Ares of application:

- Gatekeeper systems, Barrier systems
- Banks, Night counters
- Offices, authorities, car parks, etc.

Technical data :	
Power supply	
PoE (Power over Ethernet)	802.3af (Class 0 – Max. 12.95 W)
External power supply Optional	12 V DC (9-36 V DC), max. 2 A
Consumption	2 W in stand-by mode
IP parameters	
Signalling	SIP 2.0 (UDP)
Audio codec	G.711
Audio protocols	RTP (G.711)/ RTSP
IP protocols	IPv4, ARP, TCP, UDP, DHCP, HTTP/ HTTPS, SNMP, TFTP, SMTP, SIP 2.0
Audio	
	Full duplex with echo cancellation
	1 integrated loudspeaker, volume adjustable
	1 gooseneck microphone
Keys/Keypad	Numeric keypad in matrix 4x4, 4 unlabelled speed dial keys for free allocation
LEDs	3 LEDs for status display
LAN Interface	1x LAN PoE 802.3af, 10/100Base-TX with Auto-MDIX, RJ45 (mounted network cable)
Mechanische properties:	
Housing	Aluminium anodized, side covers made of plastic
Dimensions (W x D x H)	253 x 167 x 45/65 mm
Operating temperature	-40 to +55 °C
Humidity	10 % to 95 % (non-condensing)
Storage temperature	-40 to +70 °C
IP rating	IP 20
Mounting	Table unit

All specifications are subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

* Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.