

Datasheet Satelco 8 Port Gigabit Ethernet Switch



Satelco 8 Port Gigabit Ethernet Switch

The Satelco 8 port Gigabit Ethernet switch is specially designed for automation control applications. It is equipped with eight 10/1000 Base-TX RJ-45 ports. It supports a redundant power supply, has a metal housing with protection class IP40 and thus ensures fast and reliable data transmission in harsh industrial environments.

Highlights:

- 8 Ports Fast Ethernet 10/1000Base-TX RJ-45
- Robust design, ensures maximum reliability and thus smooth building automation
- High operational reliability even under extreme conditions, long-term availability and flexibility
- Installation on DIN rail and quick commissioning (plug and work)

Technical data:	
Gigabit ports	8, RJ 45
Power supply	DC 12-48V, dual power in standard, optional before order: AC/DC220V single power
LEDs	5x LED indicator lights for speed, system and power status
Power consumption	<6 Watt max.
Operative temperature	-40°C to +75°C
Storage temperature	-45°C to +80°C
Humidity	5% to 95%, not condensating
Mounting	On a standard 3.5 DIN rail
Dimensions	33 mm x 144 mm x 97 mm (W x H x D)
Warranty	5 years

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.

1