



Power supply 12V / 1 A – Satelco Article no. 10124

Nominal input voltage	110 / 240 V AC 50/60 Hz
Nominal output voltage	12 V DC, 1 A (12 W)
Efficiency	75 – 78 %
Minimum load	0 Ω
Case dimensions	1 modul (M)- 17,5 x 93 x H 66mm
Service condition	continuous
Operating temperature / humidity relative	-10 °C - +50 °C / 5 % ÷ 90 % (non-condensing)
Degree of protection	IP20
Safety standards	EN60950 – 2006/95/ECC 89/336
EMC standards	EN55022/B – EN55024



Power supply 12V / 2 A – Satelco Article no. 10125

Nominal input voltage	110 / 240 V AC 50/60 Hz
Nominal output voltage	12 V DC, 2 A (24 W)
Efficiency	80 – 85 %
Minimum load	0 Ω
Case dimensions	2 modul (M)- 35 x 93 x H 66mm
Service condition	continuous
Operating temperature / humidity relative	-10 °C - +50 °C / 5 % ÷ 90 % (non-condensing)
Degree of protection	IP20
Safety standards	EN60950 – 2006/95/ECC 89/336
EMC standards	EN55022/B – EN55024



Power supply 24V / 2 A – Satelco Article no. 10126

Nominal input voltage	110 / 240 V AC 50/60 Hz
Nominal output voltage	24 V DC, 2 A (48 W)
Efficiency	86 – 89 %
Minimum load	0 Ω
Case dimensions	4 modul (M)- 70 x 93 x H 66mm
Service condition	continuous
Operating temperature / humidity relative	-10 °C - +50 °C / 5 % ÷ 90 % (non-condensing)
Degree of protection	IP20
Safety standards	EN60950 – 2006/95/ECC 89/336
EMC standards	EN55022/B – EN55024



Power supply 5VDC/1.2A – Satelco Article no. 11022

Input voltage	110 / 240 V AC 50/60 Hz
Output voltage	24 V DC, 2 A (48 W)
Efficiency	86 – 89 %
Minimum load	0 Ω
Housing	4 Modul (TE)- Housing 70 x 93 x H 66mm
Operating condition	Continuous
Ambient temperature / rel. humidity o. Condensation	-10 °C - +50 °C / 5 % ÷ 90 %
Protection class	II
Safety standards	EN60950 – 2006/95/ECC 89/336
EMC standards	EN55022/B – EN55024



Power supply USV 12V – Satelco Article no. 10653

Input voltage	230V AC, 50/60Hz
Output voltage	13.8V DC, 5.0A, (69W)
Efficiency	86 – 89 %
Minimum load	0 Ω
Housing	DIN 6M, 108 x 95 x 68mm (L x B x H)
Operating condition	Continuous
Ambient temperature / rel. humidity o. Condensation	-10° C - + 40° C / 0.. 95%
Insulation / Protection class	II / IP 20
Safety standards	EN60950 - EN55022/B – EN61000



Power supply 12V – Satelco Article no. 10349

Input voltage	100-240V, 50/60 Mz
Output voltage	12V, 4.0A
Efficiency	86 – 89 %
Minimum load	0 Ω
Housing	Continuous
Operating condition	100-240V, 50/60 Mz
Ambient temperature / rel. humidity o. Condensation	-10 °C - +50 °C / 5 % ÷ 90 %
Protection class	II
Safety standards	EN60950 - EN55022/B – EN61000

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch
 * Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as “front accessible” can be accessed by the customer.