

## Datasheet **atcom** IP PBX Voice switch

### ATCOM IP PBX IP02



- Smart Size and Desktop design
- WAN Port and LAN Port
- Support SIP Protocol

**Highly-modular, and specifically designed to improve your daily bussines communication**

ATCOM IPPBX is a SIP-based IP voice switch with a small embedded OS and rich GUI (Graphical User Interface), providing a powerful networking and corporate communication function. It allow you to effectively reach, serve and retain your users by offering a powerful combination of intelligent call-routing, call center functionality and integral desktop productivity applications. With it, users can quickly deploy an internal communication system for enterprise, as well as configure conveniently applications and value-added services on IP PBX via its GUI, to fit enterprise's own various demands. Targeting for SOHO user and SMB market with an easy to use graphical interface, IP02 provides a cost-saving solution on their telecommunication/data needs. With IP02, company with branch offices in different countries can be easily combined together to work like a virtual single office through internet.

ATCOM IP PBX is modular-design IP communication platform, multi-type interfaces can be equipped flexiably for different office communication applications, such as FXO module, FXS module, etc.

#### PBX Features:

- Voicemail
- Voicemail to Email
- Blind/Attended Transfer
- Call Forward
- Call Parking
- Do not Disturb (DND)
- Group/Directed Pickup
- Call Recording
- Call Waiting
- Call Routing
- Caller ID
- BLF Support (Busy Lamp Field)
- Music on Hold (MoH)
- Video Call
- Authentication before call outbound
- Blacklist
- Call Detail Records (CDR)
- Conference
- Ring Group
- Call Queue
- Call Back
- Interactive Voice Response (IVR)
- Intercom/Paging
- User WEB portal
- IP Restriction
- Port Forward
- VLAN
- VPN Client
- External Storage
- Storage Quota Privilege
- Auto Provisioning
- Direct Inward System Access (DISA)

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. [www.satelco.ch](http://www.satelco.ch)

## Datasheet **atcom** IP PBX Voice switch

<b>Technical Data:</b>	
<b>Hardware</b>	
LAN Port: 1	100Mbps
WAN Port: 1	100Mbps
Analog Port: 2	RJ11
<b>SIP</b>	
SIP Compatibility	SIP(RFC3261)
Concurrent calls	8
Max. Registered users supported	64
<b>Network Features</b>	
	<ul style="list-style-type: none"> <li>• DHCP Server / Client</li> <li>• Dynamic DNS (DDNS)</li> <li>• Static IP</li> <li>• VLAN (802.1Q)</li> <li>• VPN</li> <li>• Firewall</li> <li>• Port Forward</li> </ul>
<b>Power supply</b>	
	12VDC / 500mA
<b>Power consumption</b>	
	5W
<b>Installation</b>	
	Desktop or Wall mount
<b>Place of use</b>	
Storage Temperature	20°C – 65°C
Operating Temperature	0°C – 40°C
Operating Humidity	10 – 90%, non-condensing
<b>Dimensions</b>	
Dimension	100 x 100 x 28 mm
Weight	0.4 kg

\* warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.